EM844441

Observations

Los esmaltes de Cd-Se son especiales, cuyas propiedades no son comparables a las de los esmaltes convencionales. La red, la tonalidad, el brillo y otras propiedades físicas dependen principalmente de las condiciones de aplicación. Unas condiciones de proceso constantes son esenciales para obtener resultados reproducibles. Es fundamental extremar las precauciones para evitar la contaminación. Cualquier tipo de contaminación, especialmente las partículas metálicas, puede causar manchas negras en la superficie del esmalte.

Product description

Product description	EM844441
Chemical composition	FRITAS Y MATERIAS PRIMAS
Base/Formula	SiO2, B2O3, Al2O3, ZnO, BaO, SeO2, CdO,CaO, TiO2,PbO, CoO, Cr2O3

Physical and Chemical Characteristics

Physical Form	Polvo

Physical properties

Sieve Residue	< 0.5 % (on 45 microns)

Working conditions

Cycle	Traditional double firing
Firing Temperature	980ºC-1040ºC
Conditions	Disc or dipping
Use of the product	Mixed with ceramic glaze

Additional information

Standard Packaging	25 kg Plastic Bags (different types of packaging are available on request)
Safety Instructions	Check the label and MSDS
Storage time	5 years after reception, in its original package, sealed, indoor and in a temperature between 5 and 35ºC